



## DM40 WD - PROFESSIONAL WET & DRY



OEM ORIGINAL EQUIPMENT MANUFACTURERS



ELECTRONICS



LEATHER WORKING



OPTICS



- ✓ Heavy duty steel construction
- ✓ Complete steel construction

- ✓ Three powerful by pass motors with independent cooling
- ✓ Compact and mobile



### SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	3,45
Electrical protection	IP	F
Max waterlift	mmH2O	2500
Max air flow	m <sup>3</sup> /h	540
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	76



### FILTER UNIT

Filter Type		Bag
Surface - Diameter	cm <sup>2</sup> -mm	8.000-500
Material - Efficiency	IEC 60335-2-69	Polyester - L



### COLLECTION UNIT

Discharge system		Discharge valve
Capacity	lt.	120



### VOLUME

Dimensions	cm	68x63x125h
Weight	kg	50



## SUCTION UNIT

The suction is provided by three by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



## FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.



## COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels, that make it suitable for mobile service even when used on rough surfaces. Thanks to a discharge valve, it is possible to easily and safely empty the container.



## OPTIONALS

- ✓ STAINLESS STEEL COLLECTION TANK